



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	4GHz
Dielectric Withstanding Voltage	1000 V
VSWR	1.25typ
Insertion Loss	0.05* $\sqrt{f_GHz}$
Operating Temperature	-55~+165°C
Material & Coat-Plating	
Inner Conductor	Phosphor Bronze, Gold
Dielectric	PTFE
Body	Brass,Nickel
Coupling Nut	N/A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc				
		CHK					
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Mode N/BNC-KK N Female to BNC Female Adaptor				
		PRODUCT SPEC					
		APPLICATION SPEC					
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO		
		CUSTOMER DRAWING		SCALE 4: 1	SCALE 4: 1	SHEET 1 OF 1	RVE 1