

Coaxial Cable K_01252_D

Description

PTFE - 50 Ohm - double screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.31 mm
Dielectric	PTFE (Polytetrafluoroethylene)		0.83 mm
Outer conductor	Copper, Silver plated	Braid, 95%	1.33 mm
Outer conductor	Copper, Silver plated	Braid, 92 %	1.83 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	2.4 mm +/- 0.1

Print: HUBER+SUHNER K 01252 D 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.84 ns/m
Insulation resistance	$\geq 1 \times 10^8$ MQm
Min. screening effectiveness	≥ 80 dB (up to 6 GHz)
Max. operating voltage	≤ 0.5 kV _{rms} (at sea level)
Test voltage	1 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight	1.5 kg/100 m
Min. bending radius	static 15 mm
	repeated (for ≤ 50 bendings) 24 mm
	dynamic 36 mm

Environmental Data

Temperature range	-65 °C... +165 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-3,
2011/65/EU (RoHS)	compliant

Additional Information

Ordering Information

Order as K_01252_D

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group X1 1 mm / 50 Ohm

Coaxial Cable K_01252_D

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 1.3

b = 0.3327

f_{max} = 6

P at 1GHz = 111

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0,3	0,81	0,247	203
0,6	1,21	0,368	143
0,9	1,53	0,467	117
1,2	1,82	0,556	101
1,5	2,09	0,637	91
1,8	2,34	0,714	83
2,1	2,58	0,787	77
2,4	2,81	0,857	72
2,7	3,03	0,925	68
3,0	3,25	0,990	64
3,3	3,46	1,054	61
3,6	3,66	1,117	59
3,9	3,86	1,178	56
4,2	4,06	1,238	54
4,5	4,25	1,297	52
4,8	4,45	1,355	51
5,1	4,63	1,412	49
5,4	4,82	1,468	48
5,7	5,0	1,524	46
6,0	5,18	1,579	45