

4 系列可调衰减器

型号	频率范围 (GHz)	衰减步进	最大驻 波比	插入损耗 dB)	功率	衰减精度(dB)
RBS-71-1-4 RBS-71-1-4-10W	DC-1	0-71dB in 0.1dB steps	1.25	≤1.0	2W 10W	±0.3dB(0.1~1dB) ±0.4dB(1~10dB) ±0.8dB(10~60dB) ±1.5dB(≤71dB)
RBS-71-2.5-4 RBS-71-2.5-4-10W	DC-2.5		1.5	≤1.5	2W 10W	
RBS-71-3-4 RBS-71-3-4-10W	DC-3		1.6	≤1.6	2W 10W	
RBS-71-4.5-4 RBS-71-4.5-4-10W	DC-4.5		1.6	≤2.0	2W 10W	
RBS-71-6-4 RBS-71-6-4-10W	DC-6		1.8	≤2.2	2W 10W	
RBS-101-1-4 RBS-101-1-4-10W	DC-1	0-101dB in 0.1dB steps	1.25	≤1.0	2W 10W	±0.2dB(0.1~1dB) ±0.4dB(1~10dB) ±0.8dB(10~60dB) ±1.5dB(<70dB) ±3.5%(≥70dB)
RBS-101-2.5-4 RBS-101-2.5-4-10W	DC-2.5		1.5	≤1.5	2W 10W	
RBS-101-3-4 RBS-101-3-4-10W	DC-3		1.6	≤1.7	2W 10W	

连接器类型: N

尺寸: 250×87×80mm

