

6 系列可调衰减器

型号	频率范围 (GHz)	衰减步进	最大驻 波比	插入损 耗(dB)	功率	接口	衰减精度(dB)
RBS-70-4-6 RBS-70-4-6-5W	DC-4	0-70dB in 1dB steps	1.35	≤0.75	2W 5W	SMA	±0.5dB (0~9dB) ±1.0dB(10~19dB) ±1.6dB(20~70dB)
RBS-70-8-6 RBS-70-8-6-5W	DC-8		1.50	≤1.0	2W 5W	SMA	
RBS-70-12.4-6 RBS-70-12.4-6-5W	DC-12.4		1.60	≤1.25	2W 5W	SMA	
RBS-70-18-6 RBS-70-18-6-5W	DC-18		1.70	≤1.5	2W 5W	SMA	
RBS-99-4-6 RBS-99-4-6-5W	DC-4	0-99dB in 1dB steps	1.35	≤0.75	2W 5W	SMA	±0.5dB (0~9dB) ±1.0dB(10~19dB) ±1.6dB(20~70dB) ±2.5dB(71~99dB)
RBS-99-8-6 RBS-99-8-6-5W	DC-8		1.50	≤1.0	2W 5W	SMA	
RBS-99-12.4-6 RBS-99-12.4-6-5W	DC-12.4		1.60	≤1.25	2W 5W	SMA	
RBS-99-18-6 RBS-99-18-6-5W	DC-18		1.70	≤1.5	2W 5W	SMA	

连接器类型: SMA

尺寸: Φ48×160mm

